

KG97 saw with PD automatic pusher



STANDARD FEATURES - SAW

- Swivel saw head with hydraulic power down feed
- Automatic lift and material clamping
- Blade Speeds = Low: 115 fpm; High: 230 fpm
- 1 HP, 230 VAC single phase

Capacity	0°	45°	60°
Round	6.75"	4.93"	3.14"
Rectangle	6.75" x 5.90"	4.33" x 6.75"	4.00" x 2.00"
Square	6.75"	4.53"	2.00"

ADDITIONAL FEATURES - PD AUTOMATIC GAUGE

- Position controller with program memory for full automatic operation
- Magnetic linear encoder for direct measuring
- Pneumatic gripper (pusher) or stop arm (automatic stop)
- Travel speed: 20in/sec, others available upon request
- Encoder accuracy: +/- 0.001in/ft (+/- 0.1mm/m)

PD pusher gripper



ADDITIONAL FEATURES – MD50/D MANUAL STOP

- LCD digital readout with encoder (MD50D) or tape scale rule (MD50)
- Adjustable stop arm with lift and lower for material pass through
- Encoder accuracy: +/- 0.001in/ft (+/- 0.1mm/m) (MD50D)

ROLLER CONVEYOR & FLAT TABLE, RC/RH & RF

- Open conveyor, steel construction with galvanized steel rollers
- Stands with flexible height adjustment from 27-3/8 to 39-3/8in
- Capacity: 135lbs/ft (RC) or 620lbs/ft (RH)
- Width between rail: 13/15/19 inch standard, others upon request
- Plastic rollers and metal safety inserts available upon request (RC/RH)
- Solid steel top with 135lbs/ft capacity (RF)
- Overall width: 12/16/22 inch standard, others upon request (RF)

KG97 saw with MD50D manual stop & RH conveyor



MD50D carriage



PS312 controller

