

Versa-Stop System



## STANDARD FEATURES

- Guide rail with T-slots for easy retrofit
- Tool-free operation
- Precision-ground, hardened steel contact plates
- High performance slide bearings for smooth operation
- Left or right side mounting
- Bypass feature
- Any length with any number of stops available

## SPECIFICATIONS

- Brake force: 800N
- Stop spacing: >1-3/8in
- Graduation: 1/16in / 1mm
- Total length: measuring length + 6in

Bypass Feature



## OPTIONS

- Mounting brackets (1 per 2ft recommended)
- Y-axis adjustment brackets (1 per 2ft recommended)

## ROLLER CONVEYOR, SERIES RC AND RH

- Open conveyor, steel construction with galvanized steel rollers
- Stands with flexible height adjustment from 27-3/8 to 39-3/8in
- Capacity: 135lbs/ft (RC) or 620lbs/ft (RH)
- Width between rail: 13/15/19 inch standard, others upon request
- Plastic rollers and metal safety inserts available upon request

## FLAT TABLE, SERIES RF

- Solid steel top with 135lbs/ft capacity
- Stands with flexible height adjustment from 27-3/4 to 39-3/4in
- Overall width: 12/16/22 inch standard, others upon request

Scale and indicator



Y-axis adjustment bracket



Versa-Stop System with Ironworker

